



## Iiyama Prolite T2250MTS 21.5" Multitouch LCD

### DISPLAY CHARACTERISTICS

Diagonal	21.5"
Touchtechnology	optical, multitouch (2 compatible touch points), activated by finger or stylus
Panel	TN
Glass hardness	8H minimum
Display area h x w	268.11 x 476.64 mm; 10.6" x 18.8"
Response time	5 ms
Contrast	1000 : 1 typical
Brightness	260 cd/m <sup>2</sup> typical
Brightness	300 cd/m <sup>2</sup> max.
Viewing zone	horizontal/vertical: 170°/ 160°; right/left: 85°/ 85°; up/down: 85°/ 75°
Viewing zone CR>5	horizontal/vertical: 178°/ 178°; right/left: 89°/ 89°; up/down: 89°/ 89°
Display colour	16.7 million
Pixel pitch h x v	0.248 x 0.248 mm
Native resolution	Full HD 1080p, 1920 x 1080 ( 2.1 megapixel)
Horizontal sync	31 - 82 KHz

Vertical sync 56 - 75 Hz

Synchronization Separate Sync

Aspect ratio 16 : 9

Light transmittance 88%

### INTERFACES CONNECTORS

Analog input connector D-Sub

Digital input connector DVI-D

HDCP yes

Inputs USB

### SPECIAL FEATURES

Plug & Play VESA DDC2B™

Controls On-Screen-Display in 8 languages (EN, FR, DE, IT, JP, PL, NL, RU) and 5 front controls (Power, Au down/ Volume, Meu/ Select)

User controls brightness, contrast, image control (auto adjust, H. position, V. position, clock, phase, sharpness), col position, timeout), other (language, input, speaker volume, information), reset, exit

Speakers 2 x 1 W (Stereo)

Anti-theft-device Kensington-lock™ prepared

Safety CE, TÜV/Bauart, VCCI-B

Tilt angle 20° up; 3° down

VESA mounting 100 mm

Colour Black

### ACCESSORIES

Driver Windows® 7

Included accessories power cable, D-Sub cable, DVI-D cable, audio cable, USB cable, stand, stylus, quick start guide

### POWER MANAGEMENT

Power supply AC 100 - 240 V, 50 / 60 Hz

Power Supply Unit internal

Power usage 44 W typical; max. 1 W in Power management mode

Power management VESA DPMS

### DIMENSIONS & WEIGHT

Dimensions w x h x d 513 x 419 x 263 mm

Weight 6 kg

access

the exhibition specialists

01793 613088 | sales@accessdisplays.co.uk  
www.accessdisplays.co.uk

